

## RIO FILLER

### Indoor & Outdoor Emulsion Putty

#### DESCRIPTION:

High quality Indoor & outdoor emulsion putty that has the following exceptional features:

- Exceptional non-yellowing whiteness.
- Ease to apply.
- Highly washable.
- Chalking resistant.
- Easy sand ability.
- High spreading rate.

#### Technical data:

Color White.

Specific Gravity  $1.55 \pm 0.1$  gm. /cm<sup>3</sup>.

Viscosity 60-80 Poise/ 25° C.

Drying Time

- Surface Dry: within 30 minutes.
- Dry to sand: within 3 hours.

Film Thickness 120 – 200 micron.

#### Theoretically spreading rate:

$2 \pm 1$  m<sup>2</sup>/l at dry film thickness 50 microns  
(the porosity of the surface, type of surface, application method, film thickness affect the mentioned spreading values)

#### Application:

- Clean surface well from dust and other dirt.
- New and gypsum surfaces at 1<sup>st</sup> apply :  
1-should be washed with water  
2-apply 1 coat using Rio Seal
- apply 3 layers of Rio Filler Putty

#### Validity & storage conditions:

- 24 months from production date in dry place & away from direct exposure to sun light in originally closed containers.

#### Safety Precautions:

The MSDS of the products expresses necessary data for safety storage& handling.

#### Country of origin:

Egypt



28-Jul-18