

RIO Seal 5060

ACRYLIC EMULSION SEALER

DESCRIPTION:

High quality acrylic emulsion sealer that has the following exceptional features:

- Exceptional non-yellowing whiteness.
- Excellent adhesion.
- Excellent filling & sealing power.
- Chalking resistant.
- High spreading rate.

Technical data:

Color White.

Specific Gravity 1.45 ± 0.15 gm. /cm³.

Viscosity 120 ± 15 KU/ 25° C.

Drying Time

- Surface Dry: within 30 minutes.
- Through Dry: within 3 hours.

Film Thickness 100– 150 micron.

Dilution using Fresh water

Thinning ratio max 50%.

Theoretically spreading rate:

7-10 m²/l at dry film thickness 30 microns (the porosity of the surface, type of surface, application method, film thickness affect the mentioned spreading values)

Application:

- Clean surface well from dust and other dirt.
- New and gypsum surfaces at 1st apply :
1-should be washed with water
2-apply 1 coat using Rio Seal before
- apply 3 layers of Rio Filler Putty
- Apply 2 coat of Rio Tex 5050 as under coat.

Validity & storage conditions:

- 24 months from production date in dry place & away from direct exposure to sun light in originally closed containers.

Safety Precautions:

The MSDS of the products expresses necessary data for safety storage& handling.

Country of origin:

Egypt

