

[Type here]

# SPEEDO

## N.C. WOOD VARNISH

### DESCRIPTION:

- Highly quality wood nitro cellulosic varnish used to coat & finish wood surfaces.
- High yellowing resistance .
- Excellent hardness.
- Fast dry.
- Available in different types of gloss range (5% & 25% & 45% & > 95%)
- Please read the technical data sheet of the product to choose the required gloss.
- Air pressure 4 bars , nozzle 1.5 mm
- Spray multiple thin layers ,time between each layer shouldn't be less than 15 min
- Surface dry is in 15 min ,complete dry is less than 2 hours to handle the coated item

### Technical data:

Color Clear -light.

Specific Gravity  $1 \pm 0.1$  gm. /cm<sup>3</sup>.

Viscosity 2000 - 4000 centipoise / 25° C.

Drying Time

- Surface Dry: within 10 minutes.
- Complete Dry: within 1 hours.

Film Thickness 60 – 80 micron.

Dilution N.C. thinner

### Theoretically spreading rate:

$9.5 \pm 0.2$  m<sup>2</sup>/l at dry film thickness 30 microns  
(the porosity of the surface, type of wood, application method, film thickness affect the mentioned spreading values)

### Application:

- Clean surface well and prepare the surface using suitable sealer(Extra sealer)
- Sand surface using sand paper minimum grit 120 to prepare it
- Dilute sealer with suitable N.C. thinner to adjust viscosity according to the way of application
- Preferable to use air spray gun in application

### Validity & storage conditions :

- 24 months from production date in dry place & away from direct exposure to sun light in originally closed containers.

### Safety Precautions:

The MSDS of the products expresses necessary data for safety storage& handling.

### Country of origin:



Egypt

Headquarter: 61 El Mariotiah Road, besides Siag Hotel, Giza, Egypt.

Factory: 1<sup>st</sup> Industrial Zone, 6<sup>th</sup> Of October, Giza, Egypt.

Tel.: +20 1146448884

[www.kaizenpaints.com](http://www.kaizenpaints.com)

[info@kaizenpaints.com](mailto:info@kaizenpaints.com)



28-Jul-18