



RIO FLAT MATT EMULSION COATING

- Apply two coats of Rio Flat as topcoat.

DESCRIPTION:

High quality matt acrylic emulsion coating that has the following exceptional features:

- Exceptional non-yellowing whiteness and brightness.
- Alkali & Water resistance.
- Highly washable.
- Excellent hiding power.
- Chalking resistant.

Technical data:

Color White.

Specific Gravity 1.45 ± 0.1 gm. /cm³.

Viscosity 125 ± 15 KU/ 25° C.

Drying Time

- Surface Dry: within 30 minutes.
- Through Dry: within 3 hours.

Film Thickness 120 – 200 micron.

Dilution using Fresh water

Thinning ratio max. 10%.

Theoretically spreading rate:

8-10 m²/l at dry film thickness 30 microns (the porosity of the surface, type of surface, application method, film thickness affect the mentioned spreading values)

Application:

- Clean surface well from dust and other dirt.
- New and gypsum surfaces at 1st apply :
1-should be washed with water
2-apply 1 coat using Rio Seal
- apply 3 layers of Rio Filler Putty
- Apply 1coat of Rio Tex as under coat.

Validity & storage conditions:

- 24 months from production date in dry place & away from direct exposure to sun light in originally closed containers.

Safety Precautions:

The MSDS of the products expresses necessary data for safety storage& handling.

Country of origin:

Egypt



Headquarter: 61 El Mariotiah Road, besides Siag Hotel, Giza, Egypt.

Factory: 1st Industrial Zone, 6th Of October, Giza, Egypt.

Tel.: +20 1146448884

www.kaizenpaints.com

info@kaizenpaints.com