



## RIOVITO

### Acrylic Textured Emulsion Putty

#### DESCRIPTION:

High quality Indoor & outdoor Acrylic Textured Emulsion Putty that has the following exceptional features:

- Exceptional non-yellowing whiteness.
- Ease to apply.
- Highly washable.
- Chalking resistant.
- Light & weathering resistance.
- High spreading rate.
- Available in many colors
- Many types of surface roughness profile (very fine profile, Fine profile, Coarse profile)

#### Technical data:

Color available according to customer needs.

Surface roughness:

Specific Gravity  $1.55 \pm 0.1$  gm. /cm<sup>3</sup>.

Viscosity 60-80 Poise/ 25° C.

Drying Time

- Surface Dry: within 2 hours.
- complete dry: within 12 hours.

Film Thickness 150 – 1000 micron.

#### Theoretically spreading rate:

1.75 – 2.5 Kgm/m<sup>2</sup> according to film thickness (the porosity of the surface, type of surface, application method, film thickness affect the mentioned spreading values)

#### Application:

- Clean surface well from dust and other dirt.
- New cement & gypsum surfaces at 1<sup>st</sup> apply :

1-should be washed with water

2-apply 1 coat using Rio Seal

- apply 1 layers of Riovito textured Putty

#### Validity & storage conditions:

- 24 months from production date in dry place & away from direct exposure to sun light in originally closed containers.

#### Safety Precautions:

The MSDS of the products expresses necessary data for safety storage& handling.

#### Country of origin:

Egypt

Headquarter: 61 El Mariotiah Road, besides Siag Hotel, Giza, Egypt.

Factory: 1<sup>st</sup> Industrial Zone, 6<sup>th</sup> Of October, Giza, Egypt.

Tel.: +20 1146448884

[www.kaizenpaints.com](http://www.kaizenpaints.com)

[info@kaizenpaints.com](mailto:info@kaizenpaints.com)